


# VIBRATION RATED THERMAL VACUUM SYSTEMS



**ABBESS**<sup>®</sup>


INSTRUMENTS AND SYSTEMS FOR DEVELOPING  
LEADING TECHNOLOGIES, INDUSTRIAL METHODS  
& PROCESSES

Configurable systems, designed to meet your exact testing needs, Abbess TVAC Solutions offer the power and flexibility of a custom system, while providing the cost-efficiency, convenience, and quick lead times of a standard solution.



# TYPICAL FEATURES AND CAPABILITIES

**integrated system solution for testing environments**



## System Sizes:

- 18" Cube
- 24" Cube
- 36" Cube
- 48" Cube
- Larger and Custom dimensions available upon request.

## Standard Specs and Options:

- Control temperature setpoints and ramp rates from -180°C to +200°C
- Vacuum levels from Ambient down to 1E - 2 Torr (250,000 Feet)
- Designed to withstand 5 to 300hz in both X and Y directions.
- Spare ports and with multiple feedthrough options
- Calibrated vacuum gauges
- Roughing vacuum pump
  - Available with a variety of control functions
- Viewport on door
- Vent and purge valves
- Vacuum Cycle Controller with:
  - Customizable recipes
- Full integration with valves and gauges
  - Automated vacuum and temperature control
  - Data logging and remote access
- Full integration with valves and gauges
  - Automated vacuum and temperature control
  - Data logging and remote access

- Thermal capabilities of -190°C to +200°C

- Transportation Testing

- Altitude Simulation

- ASTM Standards


- SMC Standards

- MIL-STD Standard

- Custom PLC's and data acquisition




# THERMAL TEST DATA



Your system will feature graphs displaying the actual performance of your specific instrument. The sample graph shown here is based on real test data from various TVAC configurations.




# ALTITUDE (PRESSURE) TESTING DATA



Your system will feature graphs displaying the actual performance of your specific instrument. The sample graph shown here is based on real test data from various TVAC configurations.

## Vacuum Feedthroughs




## Vacuum Compatible Lights



Available in two sizes: 30" and 17"


- Operating Pressure: Ambient to  $10E-7$  Torr
- Operating Temperature Range:  $-190^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$
- Max Storage Temperature Range:  $-190^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$

## Ln2 Cold Finger



- Different sleeve materials are available depending on your application.

## Ln2 Scavenger Plate



- When testing spacecraft or equipment under the vacuum and thermal conditions of space, the scavenger plate helps absorb any outgassing from materials inside the chamber.

## Standard Altitude (Vacuum) Control System



- Included with all thermal vacuum systems
- Customizable recipes
- Full system integration
- Automated vacuum & temperature control
- Data logging